

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (original) A method of allocating switch requests within a packet switch, the method comprising the steps of
 - (a) generating switch request data for each input port indicative of the output ports to which data packets are to be transmitted;
 - (b) processing the switch request data for each input port to generate request data for each input port-output port pairing; and
 - (d) generating an allocation plan by sorting the request data R relating to each of the input/output pairs in terms of their queue length, and
 - (e) for each input/output pair, considered in the sorted order, allocating as many of the requests in the queue as can be accommodated in the remaining time slots.
2. (original) A method of packet switching wherein the packets are switched on the basis of the allocated routing, and to a packet switch in which the input port-output port routing is allocated in accordance with claim 1, and packets are switched from an input port to a specified output port in accordance with the allocated routing.
3. (currently amended) A method according to claim 1 ~~or 2~~, in which unallocated switch requests are reserved for use in the next phase of switch request allocation, or abandoned if they have exceeded a predetermined expiry time.
4. (currently amended) A method according to claim 1, ~~2 or 3~~, comprising a preliminary stage in which the number of requests for each input or output port is reduced by a factor such that the number of requests relating to that port is no greater than the number of available time slots.

5. (currently amended) A method according to claim 1, ~~2 or 3~~, comprising a preliminary stage in which the number of requests in respect of each input/output pair are reduced by a single common factor such that the number of requests relating to all ports is no greater than the number of available time slots.
6. (currently amended) A method of packet switching wherein the input port-output port routing is allocated according to the method of ~~any preceding claim~~ claim 1 and the packets are switched on the basis of the allocated routing.
7. (currently amended) A packet switch in which the input port-output port routing is allocated in accordance with the method of ~~any of claims 1 to 6~~ claim 1.
8. (original) A packet switch according to claim 7, wherein packets are switched from an input port to a specified output port in accordance with the allocated routing.